



## 6mm PPC

<b>.243"</b>	<b>6mm</b>
<b>Weight (grains)</b>	<b>Spitzer BTSP</b>
<b>Ballistic Coefficient</b>	85
<b>Sectional Density</b>	0.380
<b>COAL Tested</b>	0.206
<b>Speer Part No.</b>	2.115"
	1213

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H335	Sako	CCI BR4	25.5	2703	29.5 C	3156
Hodgdon BL-C(2)	Sako	CCI BR4	26.5	2858	28.5 C	3098
Hodgdon H322	Sako	CCI BR4	26.0	2878	28.0 C	3083
IMR 4198	Sako	CCI BR4	23.5	2838	25.5 C	3068
Alliant Reloder 7	Sako	CCI BR4	22.0	2633	24.0	2863
Winchester 748	Sako	CCI BR4	27.0	2625	29.0 C	2838
IMR 4320	Sako	CCI BR4	25.0	2623	27.0 C	2815

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*