



6mm PPC

.243"	6mm
Weight (grains)	Spitzer SP Hot-
Ballistic Coefficient	Cor®
Sectional Density	90
COAL Tested	0.365
Speer Part No.	0.218
	2.115"
	1217

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H335	Sako	CCI BR4	25.0	2601	29.0 C	3031
Hodgdon H322	Sako	CCI BR4	25.5	2718	27.5 C	2958
Hodgdon BL-C(2)	Sako	CCI BR4	26.0	2714	28.0 C	2945
IMR 4198	Sako	CCI BR4	23.0	2699	25.0 C	2916
Winchester 748	Sako	CCI BR4	26.5	2505	28.5 C	2712
IMR 4320	Sako	CCI BR4	24.5	2463	26.5 C	2678
IMR 4895	Sako	CCI BR4	23.5	2412	25.5 C	2603
IMR 4064	Sako	CCI BR4	23.5	2308	25.5 C	2510

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load