



7-30 Waters

.284"	7mm Spitzer SP Hot- Cor®	7mm Spitzer BTSP
Weight (grains)	130	130
Ballistic Coefficient	0.368	0.424
Sectional Density	0.230	0.230
COAL Tested	2.550"	2.710"
Speer Part No.	1623	1624

NOTE: Do not use pointed bullets in tubular magazines

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 2000-MR	Federal	Federal 210	36.0	2457	40.0 C	2701
Alliant Reloder 15	Federal	CCI 200	31.5	2253	35.5	2609
Alliant AR-Comp	Federal	Federal 210	30.4	2369	33.7	2586
Hodgdon H335	Federal	CCI 250	29.0	2030	33.0	2583
Alliant Power Pro Varmint	Federal	Federal 210	30.2	2359	33.5	2570
Vihtavuori N135	Federal	CCI 200	28.5	2148	32.5	2532
Hodgdon H4895	Federal	CCI 200	30.0	2241	34.0	2514
Hodgdon BL-C(2)	Federal	CCI 250	32.0	2320	36.0	2510
IMR 3031	Federal	CCI 200	29.0	2320	33.0	2509
Winchester 748	Federal	CCI 250	31.0	2096	35.0	2487
Accurate 2015	Federal	CCI 200	26.0	2206	30.0	2480
IMR 4166	Federal	Federal 210	28.7	2198	31.7	2417
Accurate 2230	Federal	CCI 250	26.0	2039	30.0	2396

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load