



7mm-08 Remington

.284"	7mm Spitzer BTSP	7mm Spitzer SP Hot-Cor®	7mm Grand Slam® SP/CANN
Weight (grains)	145	145	145
Ballistic Coefficient	0.472	0.416	0.353
Sectional Density	0.257	0.257	0.257
COAL Tested	2.730"	2.730"	2.775"
Speer Part No.	1628	1629	1632

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 19	Remington	CCI 200	47.0	2692	51.0 C	2933
Winchester 760	Remington	CCI 250	45.0	2628	49.0	2920
Hodgdon H4350	Remington	CCI 200	44.0	2707	48.0 C	2911
Alliant Reloder 16	Federal	Federal 210	41.3	2615	45.9 C	2872
Accurate 4350	Remington	CCI 200	44.0	2644	48.0 C	2843
IMR 4350	Remington	CCI 200	44.0	2644	48.0	2841
Alliant Power Pro 4000-MR	Federal	Federal 210	43.1	2632	47.5 C	2833
Hodgdon H414	Remington	CCI 250	43.0	2560	47.0	2814
Ramshot Big Game	Federal	Federal 210	40.1	2584	44.1	2798
Alliant Reloder 17	Federal	Federal 210	40.5	2528	44.9	2787
Vihtavuori N165	Remington	CCI 200	47.0	2553	51.0 C	2781
Vihtavuori N550	Federal	Federal 210	38.5	2492	42.8	2780
Accurate 2520	Remington	CCI 250	38.0	2519	42.0	2772
Alliant Power Pro 2000-MR	Federal	Federal 210	37.5	2524	41.6	2769
Hodgdon H380	Remington	CCI 250	42.0	2520	46.0	2739
Accurate 3100	Remington	CCI 200	45.0	2480	49.0 C	2725
IMR 4895	Remington	CCI 200	37.0	2507	41.0	2724
Hodgdon Varget	Remington	CCI 200	37.0	2473	41.0	2707
Alliant Reloder 15	Remington	CCI 200	37.0	2458	41.0	2705

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load