



7mm Mauser (7x57mm)

.284"	7mm
	TNT® HP
Weight (grains)	110
Ballistic Coefficient	0.384
Sectional Density	0.195
COAL Tested	2.985"
Speer Part No.	1616

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Winchester 760	Remington	CCI 250	50.0	2983	54.0 C	3304
Alliant Power Pro 2000-MR	Federal	Federal 210	46.9	2984	50.9	3197
Hodgdon H414	Remington	CCI 250	50.0	2881	54.0 C	3191
Hodgdon Varget	Federal	Federal 210	42.8	2944	46.9	3152
IMR 4064	Remington	CCI 200	44.0	2792	48.0	3146
Alliant Reloder 15	Remington	CCI 200	44.0	2820	48.0	3141
IMR 3031	Remington	CCI 200	42.0	2795	46.0	3131
Alliant Power Pro Varmint	Federal	Federal 210	41.9	2930	45.3	3124
Vihtavuori N140	Remington	CCI 200	43.5	2757	47.5	3088
Alliant AR-Comp	Federal	Federal 210	41.2	2906	44.4	3085
IMR 4166	Federal	Federal 210	41.6	2872	45.3	3085
Accurate 2700	Remington	CCI 250	47.0	2755	51.0 C	3068
Hodgdon H380	Remington	CCI 250	46.0	2685	50.0 C	2991
IMR 4320	Remington	CCI 200	43.0	2633	47.0	2983
Hodgdon BL-C(2)	Remington	CCI 250	41.0	2631	45.0	2964
Hodgdon H4895	Remington	CCI 200	40.5	2692	44.5	2948
IMR 4895	Remington	CCI 200	40.0	2614	44.0	2945

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load