



## 7mm Mauser (7x57mm)

.284"	7mm Spitzer SP Hot- Cor®	7mm Spitzer BTSP
Weight (grains)	130	130
Ballistic Coefficient	0.368	0.424
Sectional Density	0.230	0.230
COAL Tested	2.800"	2.800"
Speer Part No.	1623	1624

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H414	Remington	CCI 250	46.0	2680	50.0 C	3003
Winchester 760	Remington	CCI 250	46.0	2657	50.0 C	2994
Alliant Reloder 17	Federal	Federal 210	44.5	2754	48.1 C	2961
Alliant Power Pro 2000-MR	Federal	Federal 210	44.0	2768	47.5	2957
Alliant Reloder 15	Remington	CCI 200	41.0	2654	45.0	2954
Accurate XMR 4350	Remington	CCI 200	47.0	2624	51.0 C	2939
Hodgdon H4350	Remington	CCI 200	46.0	2661	50.0 C	2930
IMR 4064	Remington	CCI 200	42.0	2583	46.0	2910
Alliant Reloder 22	Remington	CCI 200	49.0	2633	53.0 C	2899
IMR 4350	Remington	CCI 200	46.0	2614	50.0 C	2895
Alliant Reloder 19	Remington	CCI 200	48.0	2642	52.0 C	2894
IMR 4320	Remington	CCI 200	41.0	2593	45.0	2888
Alliant Power Pro Varmint	Federal	Federal 210	39.5	2707	42.3	2865
IMR 4166	Federal	Federal 210	38.5	2651	41.4	2830
Alliant AR-Comp	Federal	Federal 210	38.0	2659	40.9	2826
IMR 3031	Remington	CCI 200	39.0	2521	43.0	2824
IMR 4895	Remington	CCI 200	38.0	2506	42.0	2808
Vihtavuori N140	Remington	CCI 200	38.0	2515	42.0	2785
IMR SR 4759 (reduced load)	Remington	CCI 200	18.0	1658	22.0	2014

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load