



7mm Mauser (7x57mm)

.284"	7mm Spitzer BTSP	7mm Spitzer SP Hot-Cor®	7mm Grand Slam® SP/CANN
Weight (grains)	160	160	160
Ballistic Coefficient	0.519	0.504	0.389
Sectional Density	0.283	0.283	0.283
COAL Tested	3.000"	3.000"	2.960"
Speer Part No.	1634	1635	1638

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 4000-MR	Federal	Federal 210	43.4	2471	47.4	2669
Alliant Reloder 16	Federal	Federal 210	41.2	2482	44.9	2659
Alliant Reloder 17	Federal	Federal 210	40.4	2460	44.0	2646
Winchester 760	Remington	CCI 250	42.0	2393	46.0	2635
Hodgdon H414	Remington	CCI 250	42.0	2384	46.0	2611
IMR 4064	Remington	CCI 200	38.0	2281	42.0	2602
Alliant Reloder 19	Remington	CCI 200	45.0	2331	49.0 C	2598
IMR 4831	Remington	CCI 200	44.0	2300	48.0 C	2576
Accurate 4350	Remington	CCI 200	43.0	2273	47.0 C	2547
IMR 4350	Remington	CCI 200	42.0	2280	46.0 C	2542
Alliant Reloder 22	Remington	CCI 200	45.0	2254	49.0 C	2541
IMR 4451	Federal	Federal 210	40.4	2358	43.8	2529
Hodgdon H4350	Remington	CCI 200	42.0	2270	46.0 C	2528
IMR 4895	Remington	CCI 200	35.0	2212	39.0	2492
IMR 4320	Remington	CCI 200	36.0	2156	40.0	2443
Accurate 3100	Remington	CCI 200	42.0	2160	47.0 C	2420
IMR 4198 (reduced load)	Remington	CCI 200	21.0	1651	25.0	1950

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load