



7mm Remington Magnum

0.284"	7mm Spitzer BTSP	7mm Spitzer SP Hot-Cor®	7mm Grand Slam® SP/CANN
Weight (grains)	145	145	145
Ballistic Coefficient	0.472	0.416	0.353
Sectional Density	0.257	0.257	0.257
COAL Tested	3.280"	3.280"	3.235"
Speer Part No.	1628	1629	1632

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Federal	Federal 215	63.2	2853	69.7	3167
Alliant Reloder 19	Remington	CCI 250	63.0	2948	67.0	3153
Alliant Reloder 22	Remington	CCI 250	64.0	2919	68.0	3136
Alliant Reloder 25	Federal	Federal 215	65.5	2805	72.5	3106
IMR 7828	Remington	CCI 250	65.0	2974	69.0	3103
Alliant Reloder 23	Federal	Federal 215	60.8	2861	66.8	3101
Hodgdon H1000	Remington	CCI 250	69.0	2910	73.0 C	3090
IMR 4831	Remington	CCI 250	59.0	2920	63.0	3081
IMR 4350	Remington	CCI 250	56.0	2881	60.0	3070
Alliant Reloder 17	Federal	Federal 215	54.0	2867	59.4	3060
Hodgdon H870	Remington	CCI 250	76.0	2860	80.0	3037
Vihtavuori N165	Remington	CCI 250	64.0	2828	68.0	3019
Accurate 4350	Remington	CCI 250	60.0	2837	64.0	3015
Winchester 760	Remington	CCI 250	54.0	2819	58.0	3012
Accurate 3100	Remington	CCI 250	62.0	2826	66.0	3008
Hodgdon H4350	Remington	CCI 250	59.0	2801	63.0	2987
Hodgdon H4831SC	Remington	CCI 250	59.5	2835	63.5	2981
IMR SR 4759 (reduced load)	Remington	CCI 250	24.0	1811	28.0	2112

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load