



7mm Remington Magnum

| .284" | 7mm Spitzer BTSP | 7mm Spitzer SP Hot-Cor® | 7mm Grand Slam® SP/CANN |
|-----------------------|---------------------|-------------------------------|-------------------------------|
| Weight (grains) | 160 | 160 | 160 |
| Ballistic Coefficient | 0.519 | 0.504 | 0.389 |
| Sectional Density | 0.283 | 0.283 | 0.283 |
| COAL Tested | 3.280" | 3.280" | 3.225" |
| Speer Part No. | 1634 | 1635 | 1638 |

| Propellant | Case | Primer | START CHARGE | | MAXIMUM CHARGE | |
|----------------------------|-----------|-------------|-----------------|----------------------------|-----------------|----------------------------|
| | | | Weight (grains) | Muzzle Velocity (feet/sec) | Weight (grains) | Muzzle Velocity (feet/sec) |
| Alliant Reloder 33 | Federal | Federal 215 | 72.0 | 2742 | 79.2 C | 3049 |
| Alliant Reloder 25 | Remington | CCI 250 | 66.0 | 2875 | 70.0 | 3012 |
| Ramshot Magnum | Federal | Federal 215 | 64.3 | 2744 | 71.0 | 2999 |
| Alliant Reloder 26 | Federal | Federal 215 | 60.0 | 2698 | 66.3 | 2989 |
| Alliant Reloder 22 | Remington | CCI 250 | 61.0 | 2773 | 65.0 | 2976 |
| Hodgdon H870 | Remington | CCI 250 | 75.0 | 2819 | 79.0 | 2970 |
| IMR 7828 | Federal | Federal 215 | 59.2 | 2738 | 65.4 | 2961 |
| Alliant Reloder 23 | Federal | Federal 215 | 58.1 | 2705 | 64.2 | 2946 |
| Alliant Reloder 19 | Remington | CCI 250 | 60.0 | 2729 | 64.0 | 2941 |
| Hodgdon H1000 | Remington | CCI 250 | 65.0 | 2761 | 69.0 | 2936 |
| IMR 4831 | Remington | CCI 250 | 57.0 | 2784 | 61.0 | 2915 |
| Hodgdon H4350 | Remington | CCI 250 | 57.0 | 2735 | 61.0 | 2904 |
| IMR 4350 | Remington | CCI 250 | 54.0 | 2725 | 58.0 | 2901 |
| Alliant Reloder 17 | Federal | Federal 215 | 51.0 | 2667 | 56.7 | 2890 |
| Accurate 8700 | Remington | CCI 250 | 75.0 | 2736 | 79.0 | 2870 |
| Accurate 3100 | Remington | CCI 250 | 60.0 | 2691 | 64.0 | 2869 |
| Vihtavuori N165 | Remington | CCI 250 | 60.0 | 2692 | 64.0 | 2867 |
| Hodgdon H4831SC | Remington | CCI 250 | 58.0 | 2711 | 62.0 | 2853 |
| Accurate 4350 | Remington | CCI 250 | 57.0 | 2680 | 61.0 | 2849 |
| IMR SR 4759 (reduced load) | Remington | CCI 250 | 26.0 | 1770 | 30.0 | 2067 |

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load