



7mm Shooting Times Westerner

.284"	7mm Spitzer BTSP	7mm Spitzer SP Hot-Cor®	7mm Grand Slam® SP/CANN
Weight (grains)	145	145	145
Ballistic Coefficient	0.472	0.416	0.353
Sectional Density	0.257	0.257	0.257
COAL Tested	3.600"	3.600"	3.550"
Speer Part No.	1628	1629	1632

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 33	Federal	Federal 215	80.5	2945	89.5	3289
Alliant Reloder 22	Remington	CCI 250	75.0	3184	77.0	3273
Alliant Reloder 25	Remington	CCI 250	76.0	3122	80.0	3273
Alliant Reloder 26	Federal	Federal 215	69.8	2912	77.4	3249
IMR 7977	Federal	Federal 215	74.2	2928	82.2	3239
IMR 7828	Remington	CCI 250	72.0	3079	76.0	3228
Hodgdon H1000	Federal	Federal 215	72.8	2929	80.8	3223
Alliant Reloder 23	Federal	Federal 215	67.8	2935	75.0	3215
Alliant Power Pro 4000-MR	Federal	Federal 215	65.5	2921	72.8	3212
Accurate 3100	Remington	CCI 250	76.0	3126	78.0	3201
Hodgdon H4350	Remington	CCI 250	66.0	3016	70.0	3159
IMR 4350	Remington	CCI 250	67.5	3073	69.5	3154
IMR 4831	Remington	CCI 250	69.0	3082	71.0	3149
Hodgdon H414	Remington	CCI 250	62.0	2940	66.0	3052

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load