



7mm Winchester Short Magnum

.284"	7mm
	TNT® HP
Weight (grains)	110
Ballistic Coefficient	0.384
Sectional Density	0.195
COAL Tested	2.800"
Speer Part No.	1616

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 16	Federal	Federal 215	62.1	3230	68.9	3587
Alliant Power Pro 4000-MR	Federal	Federal 215	64.1	3250	71.0	3581
Alliant Reloder 17	Federal	Federal 215	61.4	3258	68.2	3559
Accurate 4350	Federal	Federal 215	64.0	3182	71.2	3535
IMR 4451	Federal	Federal 215	61.9	3177	68.7	3492
Winchester 760	Winchester	CCI 250	65.0	3260	69.0	3425
Alliant Reloder 19	Winchester	CCI 200	68.0	3192	72.0	3392
IMR 4350	Winchester	CCI 200	64.0	3185	68.0	3391
IMR 4064	Winchester	CCI 200	56.0	3207	60.0	3385
Hodgdon H4831SC	Winchester	CCI 200	70.0	3201	74.0	3376
Hodgdon H4350	Winchester	CCI 200	63.0	3200	67.0	3363
Vihtavuori N540	Winchester	CCI 200	57.0	3167	61.0	3357
Alliant Reloder 15	Winchester	CCI 200	55.0	3144	59.0	3312
Accurate 5744 (reduced load)	Winchester	CCI 200	25.0	1975	27.0	2098

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load