



7mm Winchester Short Magnum

.284"	7mm Spitzer SP Hot- Cor®	7mm Spitzer BTSP
Weight (grains)	130	130
Ballistic Coefficient	0.368	0.424
Sectional Density	0.230	0.230
COAL Tested	2.775"	2.775"
Speer Part No.	1623	1624

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Federal	Federal 215	64.4	3046	71.5	3387
Alliant Reloder 23	Federal	Federal 215	63.1	3035	69.9 C	3339
Alliant Power Pro 4000-MR	Federal	Federal 215	60.7	3034	67.3	3334
Alliant Reloder 17	Federal	Federal 215	58.7	3081	64.5	3320
Alliant Reloder 16	Federal	Federal 215	58.6	3025	65.0	3312
Alliant Reloder 19	Winchester	CCI 200	63.0	3077	67.0	3230
Alliant Reloder 22	Winchester	CCI 200	63.0	3064	67.0	3228
IMR 4831	Winchester	CCI 200	60.0	3062	64.0	3228
Accurate 3100	Winchester	CCI 200	64.0	3044	68.0	3216
IMR 4350	Winchester	CCI 200	58.0	3035	62.0	3204
Hodgdon H4350	Winchester	CCI 200	56.0	3011	60.0	3172
Hodgdon H4831SC	Winchester	CCI 200	61.0	3024	65.0	3151
Vihavuori N160	Winchester	CCI 200	57.0	2995	61.0	3112
Accurate 5744 (reduced load)	Winchester	CCI 200	26.0	1990	28.0	2084

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load