



8mm-06

<b>.323"</b>	<b>8mm</b>
	<b>Semi Spitz SP Hot-Cor®</b>
<b>Weight (grains)</b>	170
<b>Ballistic Coefficient</b>	0.311
<b>Sectional Density</b>	0.233
<b>COAL Tested</b>	3.250"
<b>Speer Part No.</b>	2283

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon BL-C(2)	Winchester (reformed 30-06)	CCI 250	47.0	2513	<b>51.0</b>	2762
IMR 4064	Winchester (reformed 30-06)	CCI 200	50.0	2437	<b>54.0 C</b>	2675
Hodgdon H380	Winchester (reformed 30-06)	CCI 250	55.0	2551	<b>59.0 C</b>	2653
Winchester 760	Winchester (reformed 30-06)	CCI 250	58.0	2418	<b>62.0 C</b>	2643
IMR 4320	Winchester (reformed 30-06)	CCI 200	49.0	2406	<b>53.0</b>	2640
Winchester 748	Winchester (reformed 30-06)	CCI 250	50.0	2369	<b>54.0</b>	2619
IMR 4350	Winchester (reformed 30-06)	CCI 200	54.0	2355	<b>58.0 C</b>	2580
IMR 4831	Winchester (reformed 30-06)	CCI 200	56.0	2352	<b>60.0 C</b>	2576
IMR 4895	Winchester (reformed 30-06)	CCI 200	46.0	2303	<b>50.0</b>	2543
IMR 3031	Winchester (reformed 30-06)	CCI 200	46.0	2287	<b>50.0 C</b>	2522

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*