



9.3x62mm

.366"	9.3mm
	Semi-Spitzer SP
	Hot-Cor®
Weight (grains)	270
Ballistic Coefficient	0.361
Sectional Density	0.288
COAL Tested	3.280"
Speer Part No.	2459

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 16	Federal	Federal 210	57.6	2318	63.9 C	2523
Alliant Reloder 17	Federal	Federal 210	55.5	2249	61.5	2482
Hodgdon H414	Federal	Federal 210	59.0	2352	62.4	2473
IMR 4831	Federal	Federal 210	58.6	2241	64.8 C	2461
IMR 4350	Federal	Federal 210	55.5	2237	61.7 C	2459
Winchester 760	Federal	Federal 210	55.7	2226	61.8	2454
Alliant Power Pro 2000-MR	Federal	Federal 210	56.0	2333	59.3	2439
Alliant Reloder 15	Federal	Federal 210	51.5	2243	57.1	2438
Hodgdon H380	Federal	Federal 210	54.2	2210	60.1	2425
Winchester 748	Federal	Federal 210	53.6	2267	58.0	2419
IMR 4451	Federal	Federal 210	56.7	2205	61.8	2378
IMR 4895	Federal	Federal 210	46.8	2180	51.9	2333

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load